CLAIMS

WHAT IS CLAIMED IS:

_	1 4	41 1	
)	1. A	method	comprising:

determining whether a block of code associated with an operation has a size greater than a threshold; and

when the size is greater than the threshold, creating a method that comprises the block of code.

10

15

- 2. The method of claim 1, further comprising: replacing the block of code at a copy location with an invocation of the method.
- 3. The method of claim 1, further comprising: adding an invocation of the method at a paste location.
 - 4. The method of claim 1, further comprising:

displaying user interface options based on whether the operation is to be performed within a single part and class.

20

5. The method of claim 1, further comprising:

displaying user interface options based on whether the operation is to be performed between two parts in a single package.

- 25 6. The method of claim 1, wherein the operation comprises a copy-and-paste operation.
 - 7. The method of claim 1, wherein the operation comprises a punch-out operation.
 - 8. An apparatus comprising:

means for determining whether a block of code associated with a copy-and-paste operation has a size greater than a threshold;

means for creating a method that comprises the block of code when the size is greater than the threshold; and

5 means for replacing the block of code with an invocation of the method.

9. The apparatus of claim 8, further comprising:

means for adding the invocation of the method at a paste location.

10 10. The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on whether the copyand-paste operation is within a single part and class.

11. The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on whether the copyand-paste operation is between two parts in a single package.

12. The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on the copy-andpaste operation being between two parts in two different packages.

13. A signal-bearing medium encoded with instructions, wherein the instructions when executed comprise:

determining whether a block of code associated with a copy-and-paste operation has a size greater than a threshold;

creating a method that comprises the block of code when the size is greater than the threshold;

replacing the block of code with an invocation of the method; and adding the invocation of the method at a paste location.

20

25

14. The signal-bearing medium of claim 13, further comprising:

selecting user interface options to present based on whether the copy-and-paste operation is within a single part and class.

5

15. The signal-bearing medium of claim 13, further comprising:

selecting user interface options to present based on whether the copy-and-paste operation is between two parts in a single package.

10 16. The signal-bearing medium of claim 13, further comprising:

selecting user interface options to present based on the copy-and-paste operation being between two parts in two different packages.

17. An electronic device comprising:

15

a processor; and

a storage device encoded with instructions, wherein the instructions when executed on the processor comprise:

determining whether a block of code associated with a copy-and-paste operation has a size greater than a threshold,

20

25

creating a method that comprises the block of code when the size is greater than the threshold,

replacing the block of code at a copy location with an invocation of the method,

adding the invocation of the method at a paste location, and

when the block of code is to return a plurality of values, creating a helper class for the method, wherein the helper class returns the plurality or values.

18. The electronic device of claim 17, wherein the instructions further comprise:

selecting a user interface default option to present based on whether the copyand-paste operation is between two parts in a single package.

- 19. The electronic device of claim 17, wherein the instructions further comprise: selecting a user interface default option to present based on whether the copyand-paste operation is between two parts in a single package.
- 20. The electronic device of claim 17, wherein the instructions further comprise:
 selecting a user interface default option to present based on the copy-and-paste
 operation being between two parts in two different packages.

5